

Wall mounted unit

ATXS-K



Siesta



2 area intelligent eye



Energy saving during standby mode



Whisper quiet



Online controller via app



Multi model application

Discreet, modern Siesta unit for optimal efficiency and comfort thanks to 2 area intelligent eye

- › Discreet, modern design. Its smooth curve blends beautifully with the wall resulting in an unobtrusive presence that matches all interior décors.
- › High quality matt crystal white finish
- › Whisper quiet in operation: the operating of the unit can hardly be heard. The sound pressure level goes down to 19dBA!
- › Ideal for installation in bedrooms (20,25 class) and larger or irregular shaped living areas (35,50 class)

- › 2 area intelligent eye: air flow is sent to a zone other than where the person is located at that moment; if no people are detected, the unit will automatically switch over to the energy-efficient setting (35,50 class)
- › Online controller (optional): control your indoor from any location with an app, via your local network or internet

ATXS-K + ARXS-L(3)



Indoor unit		ATXS	20K	25K	35K	50K
Casing	Colour		White			
Dimensions	Unit	HeightxWidthxDepth	289x780x215		298x900x215	
Sound power level	Cooling/Heating		56/56	58/58	59/59	60/60
Sound pressure level	Cooling	High/Nom./Low/Silent operation	40/32/24/19	41/33/25/19	45/37/29/19	46/40/34/23
	Heating	High/Nom./Low/Silent operation	40/34/27/19	41/34/27/19	45/39/29/19	47/40/34/24
Control systems	Infrared remote control		ARC466A6		ARC466A9	



Efficiency data		ATXS + ARXS	20K	25K + 25L3	35K + 35L3	50K + 50L
Cooling capacity	Min./Nom./Max.	kW	Only available in multi model application	-/2.5/ -	1.4/3.5/4.0	1.7/5.00/5.3
Heating capacity	Min./Nom./Max.	kW		1.3/2.8/4.7	1.4/4.00/5.2	1.7/5.80/6.5
Power input	Cooling	Min./Nom./Max.		0.320/0.602/1.000	0.350/0.840/1.190	0.350/1.587/1.810
	Heating	Min./Nom./Max.		0.310/0.620/1.410	0.340/0.840/1.460	0.300/1.450/2.000
Seasonal efficiency (according to EN14825)	Cooling	Energy label		A++		
		Pdesign		2.50	3.50	5.00
	Heating (Average climate)	SEER		7.51	7.10	6.46
		Annual energy consumption		kWh	117	173
Nominal efficiency	Cooling	Energy label		A++		
		Pdesign		2.50	3.60	4.60
	Heating	SCOP	4.68	4.61	4.00	
		Annual energy consumption	kWh	747	1,094	1,608
EER	COP	Annual energy consumption	4.15	3.70	3.15	
			4.52	4.76	4.00	
			301	473	794	
Energy label	Cooling/Heating		A/A			

Outdoor unit		ARXS	25L3	35L3	50L
Dimensions	Unit	HeightxWidthxDepth	550x765x285		735x825x300
Sound power level	Cooling		59	61	62
	Heating		59	61	62
Sound pressure level	Cooling	High/Low/Silent operation	46/-/43	48/44/-	48/-/44
	Heating	High/Low/Silent operation	47/44/-	48/45/-	48/-/45
Operation range	Cooling	Ambient Min.-Max.	10~46		
	Heating	Ambient Min.-Max.	-15~18		
Refrigerant	Type/GWP		R-410A/2,087.5	R-410A/2,087.5	R-410A/2,087.5
	Charge	kg/TCO _{2eq}	1.0/2.1	1.2/2.5	1.7/3.5
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240		

EER/COP according to Eurovent 2012, for use outside EU only | Nominal efficiency: cooling at 35°/27° nominal load, heating at 7°/20° nominal load

Contains fluorinated greenhouse gases

Daikin Europe N.V. Naamloze Vennootschap · Zandvoordestraat 300 · 8400 Oostende · Belgium · www.daikin.eu · BE 0412 120 336 · RPR Oostende (Responsible Editor)



ECPEN15-035 03/15



Daikin Europe N.V. participates in the Eurovent Certification programme for Liquid Chilling Packages (LCP), Air handling units (AHU), Fan coil units (FCU) and variable refrigerant flow systems (VRF) Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com



The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin Europe N.V. Daikin Europe N.V. has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin Europe N.V. explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin Europe N.V.